

AD-A171 460

STABILITY OF LIQUID-FILLED PROJECTILES WITH UNUSUAL
CONING FREQUENCIES(U) ARMY BALLISTIC RESEARCH LAB
ABERDEEN PROVING GROUND MD C H MURPHY JUL 86


1/1


UNCLASSIFIED

BRL-MR-3530 SBI-AD-F300 802

F/G 19/1

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A



US ARMY
MATERIEL
COMMAND

ADF 300802
12
AD

MEMORANDUM REPORT BRL-MR-3530

AD-A171 460

**STABILITY OF LIQUID-FILLED
PROJECTILES WITH UNUSUAL
CONING FREQUENCIES**

Charles H. Murphy

July 1986

DTIC
FILED
AUG 9 1986
AL

DTIC FILE COPY

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

**US ARMY BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

06 8 8 041

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as an official
Department of the Army position, unless so designated by other
authorized documents.

The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT BRL-MR-3530	2. GOVT ACCESSION NO. AD-A171400	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) STABILITY OF LIQUID-FILLED PROJECTILES WITH UNUSUAL CONING FREQUENCIES		5. TYPE OF REPORT & PERIOD COVERED Final
7. AUTHOR(s) Charles H. Murphy		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Ballistic Research Laboratory ATTN: SLCBR-LF Aberdeen Proving Ground, Maryland 21005-5066		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS RDT&E 1L161102AH43
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, Maryland 21005-5066		12. REPORT DATE July 1986
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 31
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Eigenfrequency Spinning Projectile Liquid-Filled Shell Stability Analysis Liquid Payload Stewartson-Wedemeyer Theory		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) (jvs/bja) For a liquid-filled shell, a key parameter is τ , the ratio of coning frequency to spin frequency. This report considers the stability implications of τ in the "unusual" intervals $(-1,0)$ and $(1,3)$. It is shown that for a low viscosity liquid treated by the Stewartson-Wedemeyer theory there is no possibility of unstable motion in these two regions.		

TABLE OF CONTENTS

	<u>Page</u>
I. INTRODUCTION.....	5
II. INVISCID LIQUID MOMENT.....	6
III. VISCOUS MODIFICATIONS.....	9
IV. LIQUID-FILLED SHELL STABILITY.....	10
REFERENCES.....	13
APPENDIX A. COMMENTS ON REFERENCE 10.....	15
APPENDIX B. ERRATA FOR BRL MR 3194 (REFERENCE 3).....	19
LIST OF SYMBOLS.....	21
DISTRIBUTION LIST.....	25



A-1

I. INTRODUCTION

The prediction of the complete moment exerted by a spinning liquid payload on a spinning and coning projectile has been a problem of considerable interest to the Army for some time. For fully spinning liquid, the linear side moment was first computed by Stewartson¹ for an inviscid payload by use of fluid oscillation eigenfrequencies determined by the fineness ratio of the cylindrical container. Wedemeyer² introduced boundary layers on the walls of the container and was able to determine viscous corrections for Stewartson's eigenfrequencies, which could then be used in Stewartson's side moment calculation. Murphy³ then completed the linear boundary theory by including all pressure and wall shear contributions to the liquid-induced side moment. The Stewartson-Wedemeyer eigenvalue calculations have been improved for low Reynolds numbers by Kitchens *et al*⁴ through the replacement of the cylindrical wall boundary approximation by a linearized Navier-Stokes approach. Next, Gerber *et al*⁵⁻⁶ extended this linearized NS technique to compute better side moment coefficients for Reynolds numbers less than 10,000. Finally, the roll moment for a fully spun-up liquid was computed by Murphy.⁷⁻⁸

1. Stewartson, K., "On the Stability of a Spinning Top Containing Liquid," Journal of Fluid Mechanics, Vol. 5, Part 4, September 1959, pp. 577-592.
2. Wedemeyer, E. H., "Viscous Correction to Stewartson's Stability Criterion," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Report No. 1325, June 1966. (AD 489687)
3. Murphy, C. H., "Angular Motion of a Spinning Projectile with a Viscous Liquid Payload," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-03194, August 1982. (AD A118676). (See also Journal of Guidance, Control, and Dynamics, Vol. 6, July-August 1983, pp. 280-286.)
4. Kitchens, C. W., Jr., Gerber, N., and Sedney, R., "Oscillations of a Liquid in a Rotating Cylinder: Solid Body Rotation," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report BRL-TR-02081, June 1978. (AD A057759)
5. Gerber, N., Sedney, R., and Bartos, J. M., "Pressure Measurement on a Liquid-Filled Projectile: Solid Body Rotation," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report ARBRL-TR-02422, October 1982. (AD A120567)
6. Gerber, N. and Sedney, R., "Moment on a Liquid-Filled Spinning and Nutating Projectile: Solid Body Rotation," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report ARBRL-TR-02470, February 1983. (AD A125332)
7. Murphy, C. H., "Liquid Payload Roll Moment Induced by a Spinning and Coning Projectile," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report ARBRL-TR-02521, September 1983. (AD A133681) (See also AIAA Paper 83-2142, August 1983.)
8. Murphy, C. H., "A Relation Between Liquid Roll Moment and Liquid Side Moment," Journal of Guidance and Control, Vol. 8, pp. 287-288, March-April 1985.

In 1965 Greenspan⁹ published a general boundary layer theory which for a cylinder should give the same viscous correction to the eigenvalues as computed by Wedemeyer. Kudlick¹⁰ made such calculations but his work was marred by an incorrectly derived formula based on Greenspan's correct general result.* Kudlick also considered only half the axial eigenfunctions and neglected those which are important for coning motion of a projectile.

A primary parameter of the Stewartson-Wedemeyer (SW) theory is τ , the ratio of the coning frequency to the spin frequency. For conventional spinning projectiles, τ lies between zero and one-half. For this reason, all theoretical and experimental work has concentrated on this range of τ . D'Amico¹¹ considered the possibility of unusual projectiles with τ greater than one and computed Stewartson eigenfrequency tables for $1.1 < \tau < 1.7$. Spinning finned missiles can have coning motions in an opposite direction to the spin and for these missiles τ can be negative.

It is the purpose of this report to consider the stability implication of the SW theory for negative τ and $\tau > 1$. This will be done by first deriving the SW prediction for liquid side moment and then inserting this moment in the projectile dynamics to obtain specific conclusions on the influence of the liquid payload on projectile stability.

II. INVISCID LIQUID MOMENT

We will consider a spinning projectile** performing a coning or spiraling motion. In nonrolling coordinates the angular motion has the form:

$$\ddot{\beta} + i \ddot{\alpha} = \hat{K} e^{S\phi} \quad (2.1)$$

where $\phi = \dot{\phi}t$

$$S = (\epsilon + i)\tau$$

$\dot{\phi}$ is the spin rate.

*In Appendix A, correct formulas are derived in Kudlick's notation.

**For simplicity only positive spin will be considered.

9. Greenspan, H. P., "On the General Theory of Contained Rotating Fluid Motions," Journal of Fluid Mechanics, Vol. 22, Part 3, pp. 449-462, 1965.
10. Kudlick, M. D., On the Transient Motions of a Contained, Rotating Fluid, Ph.D Thesis, Department of Mathematics, Massachusetts Institute of Technology, February 1966.
11. D'Amico, W. P., "Stability of Satellites and Unusual Aerodynamic-Shaped-Vehicles Carrying Liquid Payloads," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-2392, June 1974. (AD 921454L)

According to Eq. (2.1), τ is the ratio of the coning frequency to the spin frequency. If the projectile is coning in the direction of spin, τ is positive and positive ϵ indicates a growing motion. If the coning motion opposes the spin, τ is negative and positive ϵ indicates a decaying motion.

The liquid moment induced by the coning motion of Eq. (2.1) can be expressed in terms of a dimensionless liquid moment coefficient.

$$M_{Ly} + iM_{Lz} = m_L a^2 \phi^2 \tau C_{LM} \hat{K} e^{s\phi} \quad (2.2)$$

where $C_{LM} = C_{LSM} + iC_{LIM}$ and other symbols are defined in the List of Symbols. The imaginary part of this coefficient induces a motion in the plane of the angle of attack and is called the liquid in-plane moment coefficient while the real part causes a motion out of this plane and is called the liquid side moment coefficient.

The inviscid liquid moment can be computed from appropriate expressions in Reference 3. Consider a fully filled cylinder with diameter $2a$ and height $2c$, whose center is located at the projectile's center of mass. If we neglect a small centripetal pressure term, the liquid moment coefficient is

$$\begin{aligned} \tau C_{LM} = & \frac{1}{2} (a/2c\hat{K}) \left\{ a^{-2} \int_{-c}^c [e^{i\phi_p} C_p]_{r=a} x \, dx \right. \\ & \left. - 2a^{-3} \int_0^a [e^{i\phi_p} C_p]_{x=c} r^2 dr \right\} \end{aligned} \quad (2.3)$$

where $e^{i\phi_p} C_p = -(c/a)\hat{K} \sum a_k E_k \sin(\frac{k\pi x}{2c}) J_1(k\hat{\lambda} r/c)$

$$\hat{\lambda}^2 = -\frac{s^2 - 2is + 3}{(s-1)^2} (\pi/2)^2$$

$$a_k = 8(k\pi)^{-2} (-1)^{(k-1)/2} \quad k = 1, 3, 5, \dots$$

$$E_k = 2s(s-3i)g^{-1}$$

$$g(s, f^*) = \frac{(s+1)}{s-1} J_1(\hat{\lambda}/f^*) - (\hat{\lambda}/f^*) J_0(\hat{\lambda}/f^*)$$

$$f^* = c/ka$$

The k-th term in the series expansion of the liquid moment coefficient can be computed to be:

$$\tau C_{LM_k} = -i(c/a)^2 a_k^2 E_k \left[\frac{s}{s+1} J_1(\hat{\lambda}/f^*) + \frac{(s-1)^2}{2(s^2-2is+3)} g \right] \quad (2.4)$$

For an infinite set, $i\tau_{kn}$, of pure imaginary values of s , the denominator of E_k becomes zero and an infinite value of the inviscid liquid moment is predicted. These eigenfrequencies, τ_{kn} , are functions of the reduced fineness ratio, f^* , and have been tabulated by Stewartson¹ and others.¹¹⁻¹³ It can be shown that the eigenfrequencies lie between -1 and 3. The function g can be expanded in the vicinity of an eigenfrequency.

$$g(s, f^*) = (s - i\tau_{kn}) g_1 \quad (2.5)$$

where $g_1 = \left[\frac{\partial}{\partial s} g(s, f^*) \right]_{s=i\tau_{kn}}$

$$= \frac{-2i}{(1 - \tau_{kn})^3} \left[(1 + \tau_{kn}) + \frac{\pi^2}{2(f^*)^2} \right] [J_1(\hat{\lambda}/f^*)]_{s=i\tau_{kn}}$$

In the vicinity of τ_{kn} , E_k can be approximated by

$$E_k = \frac{2\tau_{kn}(3 - \tau_{kn})}{(s - i\tau_{kn})g_1} \quad (2.6)$$

The liquid moment coefficient for τ 's which are not near a τ_{kn} is usually quite small. For τ near a τ_{kn} , it is well approximated by*

*The formula in Reference 3 differs from this by a typographical error. An updated errata for Reference 3 is given in Appendix B.

12. Karpov, B. G., "Dynamics of Liquid Filled Shell. Aids for Designers: (a) Milne's Graph; (b) Stewartson's Tables," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-1477, May 1963. (AD 410484)
13. Frasier, J. T., "Dynamics of Liquid-Filled Shell: Aids for Designers," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-1892, December 1967. (AD 665356)

$$\begin{aligned} \tau_{LM} &= \frac{(f^*)^2 R^2}{2\pi k^2(s - i\tau_{kn})}, \quad -1 < \tau_{kn} < 1 \\ &= \frac{-(f^*)^{-2} R^2}{2\pi k^2(s - i\tau_{kn})}, \quad 1 < \tau_{kn} < 3 \end{aligned} \quad (2.7)$$

where
$$R^2 = \frac{4(2f^*)^6 |1 - \tau_{kn}|^3 \tau_{kn}^2 (3 - \tau_{kn})}{\pi^3 (1 + \tau_{kn}) [\pi^2 + 2(f^*)^2 (1 + \tau_{kn})]}$$

Values of R are also tabulated as functions of f^* in References 1, 11, 12, and 13.

III. VISCOUS MODIFICATIONS

The major difficulty with the inviscid Stewartson eigenfrequency theory is that it predicts much too large liquid moments for τ near an eigenfrequency, τ_{kn} . Wedemeyer² introduced a viscous boundary layer theory and sought to predict the resulting liquid moment by a simple manipulation of Stewartson's tables. By a very clever approach, he showed that viscous eigenvalues, s_{kn} , could be computed from Stewartson's table of inviscid eigenfrequencies, τ_{kno} , by the relations

$$s_{kn} = i\tau_{kn} + \epsilon_{kn}\tau_{kn} \quad (3.1)$$

$$\tau_{kn} = \tau_{kno} + \Delta\tau_{kn} \quad (3.2)$$

$$\epsilon_{kn}\tau_{kn} + i\Delta\tau_{kn} = i \frac{d\tau_{kn}}{df^*} f^* [\delta_a - \delta_c]_{s = i\tau_{kn}} \quad (3.3)$$

$$\delta_a = (s - i)^{-1/2} Re^{-1/2}$$

$$\delta_c = \frac{-(a/c)Re^{-1/2}}{2(1+is)} [(1 - is)(s - 3i)^{-1/2} - (3 + is)(s + i)^{-1/2}]$$

and the complex roots are selected to have positive real parts.

The derivative in Eq. (3.3) can be computed by differentiating the condition for eigenfrequencies, $(g(s, f^*) = 0)$.

$$\frac{d\tau_{kn}}{df^*} = - \left[\frac{\frac{\partial g}{\partial f^*}}{i \frac{\partial g}{\partial s}} \right]_{s=i\tau_{kn}} \quad (3.4)$$

But $\left[\frac{\partial g}{\partial s} \right]_{s=i\tau_{kn}} = g_1$

$$\left[\frac{\partial g}{\partial f^*} \right]_{s=i\tau_{kn}} = \frac{-1}{f^*} \frac{(1+\tau_{kn})(3-\tau_{kn})}{(1-\tau_{kn})^2} \left[1 + \frac{\pi^2}{4(f^*)^2} \right] J_1\left(\frac{\hat{\lambda}}{f^*}\right)_{s=i\tau_{kn}} \quad (3.6)$$

$$\therefore f^* \frac{\partial \tau}{\partial f^*} = \frac{(1-\tau_{kn})^2(3-\tau_{kn}) \left[1 + \frac{\pi^2}{4(f^*)^2} \right]}{[2(1+\tau_{kn}) + \frac{\pi^2}{(f^*)^2}]} \quad (3.7)$$

It can easily be verified that the viscous damping rate, $\epsilon_{kn}\tau_{kn}$, is always negative. Finally it is interesting to note that if Greenspan's boundary layer theory is correctly applied to a cylinder, viscous corrections to the inviscid eigenfrequency can be computed which agree with those predicted by Eq. (3.3). (See Appendix A.)

The viscous eigenvalue, s_{kn} , of Eq. (3.1) can now be used to replace the inviscid eigenvalue, $i\tau_{kn}$, in Eq. (2.7). The resulting prediction of the liquid moment has agreed very well with experiments for large Reynolds numbers.

IV. LIQUID-FILLED SHELL STABILITY

The angular motion of a spinning projectile can be represented as the sum of two coning motions. In Reference 3 the influence of the liquid moment is considered and it is shown that C_{LIM} affects the frequencies of the motion while C_{LSM} affects the damping. The precise relations are:³

$$\tau_j = \sigma/2[f_j - (-1)^j \sqrt{f_j^2 - (1/s_g)}] \quad j=1,2 \quad (4.1)$$

$$\epsilon_j = \epsilon_{aj} + (m_L a^2/I_x)[2\tau_j/\sigma - 1]^{-1} C_{LSM}(\tau_j, \epsilon_j) \quad (4.2)$$

where $\sigma = I_x/I_y$

$$f_j = 1 + (m_L a^2/I_x) C_{LIM}(\tau_j, \epsilon_j)$$

ϵ_{aj} is aerodynamic damping rate.

Equation (4.2) can be used to determine the effect of the algebraic sign of C_{LSM} on the stability of the motion. This effect can now be summarized:

(1) $\tau < 0$, positive C_{LSM} is destabilizing.

(2) $0 < \tau < 1$, positive C_{LSM} is destabilizing if $2\tau > \sigma$ and negative C_{LSM} is destabilizing if $2\tau < \sigma$.

(3) $1 < \tau$, positive C_{LSM} is destabilizing*.

For constant amplitude motion ($\epsilon = 0$), the Stewartson-Wedemeyer theory (Eqs. (2.6, 3.1)) predicts the side moment coefficient for τ near an eigenfrequency to be:

$$C_{LSM} = \frac{-(f^*)^{-2} R^2 \epsilon_{kn}}{2\pi k^2 [(\tau - \tau_{kn})^2 + \tau_{kn}^2 \epsilon_{kn}^2]}, \quad -1 < \tau_{kn} < 1$$

$$= \frac{(f^*)^{-2} R^2 \epsilon_{kn}}{2\pi k^2 [(\tau - \tau_{kn})^2 + \tau_{kn}^2 \epsilon_{kn}^2]}, \quad 1 < \tau_{kn} < 3$$
(4.3)

where $\epsilon_{kn} > 0 \quad \tau_{kn} < 0$
 $\epsilon_{kn} < 0 \quad \tau_{kn} > 0.$

According to Equation (4.3), the side moment coefficient is positive for $0 < \tau_{kn} < 1$ and is negative otherwise. Therefore, the Stewartson-Wedemeyer theory predicts a possible instability for the fast rate when τ lies in the range zero to one and no possibility of instability for any other frequencies. In other words, a low viscosity liquid can only have adverse stability effects on conventional statically unstable projectiles. The effect of very viscous liquids can not be predicted by Stewartson-Wedemeyer theory and may be adverse for the stability of any projectile.

*This depends on the very reasonable assumption¹¹ that $\sigma < 2$.

REFERENCES

1. Stewartson, K., "On the Stability of a Spinning Top Containing Liquid," Journal of Fluid Mechanics, Vol. 5, Part 4, September 1959, pp. 577-592.
2. Wedemeyer, E. H., "Viscous Correction to Stewartson's Stability Criterion," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Report No. 1325, June 1966. (AD 489687)
3. Murphy, C. H., "Angular Motion of a Spinning Projectile with a Viscous Liquid Payload," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-03194, August 1982. (AD A118676). (See also Journal of Guidance, Control, and Dynamics, Vol. 6, July-August 1983, pp. 280-286.)
4. Kitchens, C. W., Jr., Gerber, N., and Sedney, R., "Oscillations of a Liquid in a Rotating Cylinder: Solid Body Rotation," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report BRL-TR-02081, June 1978. (AD A057759)
5. Gerber, N., Sedney, R., and Bartos, J. M., "Pressure Measurement on a Liquid-Filled Projectile: Solid Body Rotation," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report ARBRL-TR-02422, October 1982. (AD A120567)
6. Gerber, N. and Sedney, R., "Moment on a Liquid-Filled Spinning and Nutating Projectile: Solid Body Rotation," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report ARBRL-TR-02470, February 1983. (AD A125332)
7. Murphy, C. H., "Liquid Payload Roll Moment Induced by a Spinning and Coning Projectile," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Technical Report ARBRL-TR-02521, September 1983. (AD A133681) (See also AIAA Paper 83-2142, August 1983.)
8. Murphy, C. H., "A Relation Between Liquid Roll Moment and Liquid Side Moment," Journal of Guidance and Control, Vol. 8, pp. 287-288, March-April 1985.
9. Greenspan, H. P., "On the General Theory of Contained Rotating Fluid Motions," Journal of Fluid Mechanics, Vol. 22, Part 3, pp. 449-462, 1965.
10. Kudlick, M. D., On the Transient Motions of a Contained, Rotating Fluid, Ph.D Thesis, Department of Mathematics, Massachusetts Institute of Technology, February 1966.
11. D'Amico, W. P., "Stability of Satellites and Unusual Aerodynamic-Shaped-Vehicles Carrying Liquid Payloads," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-2392, June 1974. (AD 921454L)

12. Karpov, B. G., "Dynamics of Liquid Filled Shell. Aids for Designers: (a) Milne's Graph; (b) Stewartson's Tables," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-1477, May 1963. (AD 410484)
13. Frasier, J. T., "Dynamics of Liquid-Filled Shell: Aids for Designers," Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Memorandum Report ARBRL-MR-1892, December 1967. (AD 665356)

APPENDIX A

COMMENTS ON REFERENCE 10

The basic error in Reference 10 is Equation [A.3]* which was used to simplify Eq. [2.15]. The result, Eq. [2.16] or (4.29) of Reference 9 is incorrect. The derivation of this equation is based on Eq. [A.4] which uses the solution for the boundary layer velocity vector, \tilde{V}_m , and applies the divergence theorem to this function. For a cylinder the boundary layer associated with flat end-walls and the cylindrical side-walls overlap and the solution for \tilde{V}_m is double-valued. The region for which these two values differ significantly from zero, is, however, quite small and the solution is a quite good approximation. For a sphere, only at the center is the function multiple-valued, but for other spheroids it is multiple-valued throughout the interior, as can be seen from the definition of ζ .

Correct calculations of the viscous correction to the eigenvalue, $s_m^{(1)}$, can be made for a cylinder by use of Eq. [2.15] if different definitions of I_1 and I_2 are used.

$$I_1 = - \int_{-1}^1 \int_0^{2\pi} \left[\lim_{\substack{\text{Re} \rightarrow \infty \\ s \rightarrow i\lambda_{mk}}} \Phi_m^* \int_0^\infty \hat{n} \times (\hat{n} \times \nabla) \cdot \tilde{V}_m d\zeta \right]_{r=r_0} r_0 d\omega dz \quad (A-1)$$

$$I_2 = -2 \int_0^{r_0} \int_0^{2\pi} \left[\lim_{\substack{\text{Re} \rightarrow \infty \\ s \rightarrow i\lambda_{mk}}} \Phi_m^* \int_0^\infty \hat{n} \times (\hat{n} \times \nabla) \cdot \tilde{V}_m d\zeta \right]_{z=1} r d\omega dr \quad (A-2)$$

If the unit vectors for Reference 10's cylindrical coordinates are $(\hat{e}_r, \hat{e}_\omega, \hat{k})$, then \hat{n} is \hat{e}_r for Eq. (A-1) and is \hat{k} for Eq. (A-2).

$$\begin{aligned} \therefore \hat{n} \times (\hat{n} \times \nabla) &= -\hat{e}_\omega r^{-1} \frac{\partial}{\partial \omega} - \hat{e}_z \frac{\partial}{\partial z}, & \hat{n} &= \hat{e}_r \\ &= -\hat{e}_r \frac{\partial}{\partial r} - \hat{e}_\omega r^{-1} \frac{\partial}{\partial \omega}, & \hat{n} &= \hat{k} \end{aligned} \quad (A-3)$$

$$\text{Now, } \Phi_m = \Phi_{mk}(r, z) e^{ik\omega} \quad (A-4)$$

$$\vec{Q}_m = (U_{mk}(r, z), V_{mk}(r, z), W_{mk}(r, z)) e^{ik\omega} \quad (A-5)$$

* [] will be used to denote equations in Reference 10.

$$\frac{\partial \hat{e}_r}{\partial \omega} = \hat{e}_\omega, \quad \frac{\partial \hat{e}_\omega}{\partial \omega} = -\hat{e}_r \quad (\text{A-6})$$

Eqs. (A-4) thru (A-6) plus Eq. [A.4] can be used to simplify Eqs. (A-1) and (A-2).

$$I_1 = +2\pi(i\lambda_{mk})^{-1/2} \int_{-1}^1 \phi_{mk} \left(ik V_{mk} + r_0 \frac{\partial W_{mk}}{\partial z} \right)_{r=r_0} dz \quad (\text{A-7})$$

$$I_2 = -2\pi \int_0^{r_0} \{ (2ip_+)^{-1/2} \left[\frac{\partial}{\partial r} (U_{mk} + iV_{mk}) + \frac{k+1}{r} (U_{mk} + iV_{mk}) \right] \right. \\ \left. + (2ip_-)^{-1/2} \left[\frac{\partial}{\partial r} (U_{mk} - iV_{mk}) - \frac{k-1}{r} (U_{mk} - iV_{mk}) \right] \right\}_{z=1} \phi_{mk} r dr \quad (\text{A-8})$$

If Eq. [7.2] for ϕ_{mk} , U_{mk} , V_{mk} and W_{mk} and Bessel function relations [C.2, C.5-C.7] are used in conjunction with Eqs. (A-7, A-8), final equations for I_1 and I_2 can be written:

$$I_1 = +iI_3 \hat{\delta}_a \quad (\text{A-9})$$

$$I_2 = -iI_3 \hat{\delta}_c \quad (\text{A-10})$$

where
$$I_3 = \frac{2\pi[k^2 + (m\pi r_0)^2][J_k(\alpha_{mk} r_0)]^2}{r_0 \lambda_{mk}} \quad (\text{A-11})$$

$$\hat{\delta}_a = \left[1 - \frac{i\lambda_{mk}}{|\lambda_{mk}|} \right] |2\lambda_{mk}|^{-1/2} \quad (\text{A-12})$$

$$\hat{\delta}_c = \frac{r_0(1+i)}{4\lambda_{mk}} \left[\frac{(2+\lambda_{mk})}{|p_-|^{1/2}} + \frac{i(2-\lambda_{mk})}{|p_+|^{1/2}} \right] \quad (\text{A-13})$$

$$p_{\pm} = \frac{\lambda_{mk}}{2} \pm 1$$

N in Reference 10 is defined as

$$N \equiv \iiint |Q|^2 dV \quad (A-14)$$

$$= (4 - \lambda_{mk}^2)^{-2} \iiint [|\nabla \phi_{mk}|^2 + \frac{4}{\lambda_{mk}^2} |k \cdot \nabla \phi_m|^2] dV$$

It is correctly computed in Eq. [C.16] to be

$$N = 2\pi \left(\frac{J_k(\alpha_{mk} r_0)}{\lambda_{mk}} \right)^2 \frac{4}{4 - \lambda_{mk}^2} \left\{ k^2 + (m \pi r_0)^2 - \frac{k \lambda_{mk}}{2} \right\} \quad (A-15)$$

$$\therefore s_{mk}^{(1)} = \frac{-(I_1 + I_2)}{N} \quad (A-16)$$

$$= i I_4 (\hat{\delta}_a - \hat{\delta}_c)$$

where

$$I_4 = \frac{-[1 - \frac{\lambda_{mk}^2}{4}] \lambda_{mk} [k^2 + (m \pi r_0)^2]}{r_0 [k^2 + (m \pi r_0)^2 - \frac{k \lambda_{mk}}{2}]} \quad (A-17)$$

Eqs. [7.7] thru [7.10] and the figures and tables at the end of Chapter 7 need to be revised in the light of the above equations.

A correspondence between the symbols of Reference 10 and that of Reference 3 is given in Table A-1

TABLE A-1

	Reference 10	Reference 3
axial wave number	m	k/2
azimuthal wave number	k	-m
radial wave number	l	n
inviscid eigenfrequency	$\lambda_{mk l}$	$\tau_{knm} - m$
viscous correction to eigenfrequency	$s_{mk l}^{(1)}$	$(c/a)[\epsilon_{knm} \tau_{knm} + i \Delta \tau_{knm}] \text{Re}^{1/2}$

reduced fineness ratio	$(2mr_0)^{-1}$	f^*
Reynolds number	R	$(c/a)^2 Re$
sidewall boundary layer parameter	$\hat{\delta}_a$	$\delta_a Re^{-1/2}$
endwall boundary layer parameter	$\hat{\delta}_c$	$\delta_c Re^{-1/2}$

As can be seen from the table, Kudlick's selection of integer values of his axial wave number, m , considers half of the possible eigenvalues, i.e., only those corresponding to the even values of Stewartson's wave number. For the forced oscillation of a cylindrical payload, $k = -1$ and m equal to odd multiples of $1/2$ provide the significant eigenvalues.

The relations of Table A-1 can be used to express I_4 in terms of the symbols of Reference 3. If this is done, it can be seen that I_4 is $(a/c)f^* \frac{\partial \tau}{\partial f^*}$ and, therefore, Eq. (A-17) gives essentially the same viscous corrections as Eq. (3.3).

APPENDIX B

ERRATA FOR BRL MR 3194 (REFERENCE 3)

1. Third term of Eq. (5.20) should contain $(s - i)$, not $(s - 1)$.
2. Second line of Eq. (6.4) should read:

$$= i (c/2a) \int_{-1}^1 \hat{x} [C_p^*]_{r=a} \hat{K}^{-1} d\hat{x} + (h/c)^2 m_{p\ell h} \quad (6.4)$$

3. Two lines after Eq. (6.4) should read

$$m_{p\ell h} = -i(c^3/2a^2h) \int_{-1}^1 C_{p0}(a, \hat{x}) d\hat{x} ; \dots$$

4. Eq. (6.12) should read:

$$\begin{aligned} m_p &= \frac{[R/f^*]^2}{2\pi k^2(s-i\tau_{kn})} & \tau_{kn} < 1 \\ &= \frac{-[R/f^*]^2}{2\pi k^2(s-i\tau_{kn})} & \tau_{kn} > 1 \end{aligned} \quad (6.12)$$

where $R = R(f^*, f)$

5. Equation at top of page 32 should read:

$$\epsilon_{kn}\tau_{kn} + i\Delta\tau_{kn} = i\left[\frac{\partial\tau_{kn}}{\partial f^*}(\delta_a - \delta_c)f^* + 2\frac{\partial\tau_{kn}}{\partial f}(f-1)\delta_a\right]$$

6. Eq. (6.15) should read:

$$(C_{LSM})_{\max} = \frac{-(R/f^*)^2}{2\pi k^2\tau_{kn}^2[\epsilon_{kn}-\epsilon]} , \quad \tau_{kn} < 1 \quad (6.15)$$

7. Third line after Eq. (6.15) should read: "somewhat more complicated since δ_a is independent of k and δ_c varies as k^{-1} for constant f^* ."
8. Fifth line after Eq. (6.15) should read: "and k^{-1} ."
9. In the second line from bottom of page 32 replace "1 to 9." by "3 to 9."
10. In the third line from top of page 33 replace "1 to 25." by "5 to 25."

11. Eq. (7.1) should read:

$$m_{vl} = i (2\pi \hat{K} Re)^{-1} e^{-s\phi} \int_{-1}^1 \int_0^{2\pi} e^{i\theta} m_{vl}^* d\theta d\hat{x} \quad (7.1)$$

12. Eq. (7.4) should read

$$m_{ve} = (2a \hat{K} Re)^{-1} \int_b^a [\hat{x} \frac{\partial}{\partial \hat{x}} (w_{sv} - i v_{sv})]_{\hat{x}=-1}^{\hat{x}=1} r dr + (h/c)^2 m_{veh} \quad (7.4)$$

where

$$m_{veh} = (2 \hat{K} Re)^{-1} (c/ah) \int_b^a [\frac{\partial}{\partial \hat{x}} (w_{sv} - i v_{sv})]_{\hat{x}=-1}^{\hat{x}=1} r dr.$$

13. Third term of Eq. (9.4) should be:

$$(s - i) \delta_a(ad) R_k''(d)$$

14. Second line after Eq. (9.8) should read:

$$m_{prh} = i(dc^3/2a^3h) \int_{-1}^1 e^{i\theta_p} c_{p0} d\hat{x}$$

15. Eq. (10.1) should read:

$$(c/a)_{av} = (c/2) \int_{-1}^1 \frac{d\hat{x}}{a(\hat{x})}$$

16. Eq. (B23) should have + sign in front of u_{s1} .

17. On Page 105 last line; replace "aerodynamic" with "liquid."

LIST OF SYMBOLS

a	radius of a right-circular cylindrical cavity containing liquid
a_k	$8(k\pi)^{-2}(-1)^{(k-1)/2}$, $k=1,3,5,\dots$
c	half-length of a right-circular cylindrical cavity containing liquid
f^*	c/ka
f_j	$1 + (m_L a^2/I_x) C_{LIM}(\tau_j, \epsilon_j)$, $j=1,2$
g	$\left(\frac{s+i}{s-i}\right) J_1\left(\frac{\hat{\lambda}}{f^*}\right) - \left(\frac{\hat{\lambda}}{f^*}\right) J_0\left(\frac{\hat{\lambda}}{f^*}\right)$
g_1	$\left. \frac{\partial g(s, f^*)}{\partial s} \right _{s=i\tau_{nk}}$
k	azimuthal wave number
m_L	mass of the liquid in the cylindrical cavity
n	radial wave number
r	radial coordinate
s	$(\epsilon+i)\tau$
s_g	gyroscopic stability factor
s_{kn}	eigenvalue of s for the liquid's (k,n)th wave mode
t	time
x	coordinate along the missile's axis of symmetry, positive forward
C_{LM}	$\frac{M_{L\tilde{y}} + i M_{L\tilde{z}}}{m_L a^2 \phi^2 \tau k e^{s\phi}}$
C_{LIM}	liquid in-plane moment coefficient; the imaginary part of C_{LM}
C_{LSM}	liquid side moment coefficient; the real part of C_{LM}
C_p	nondimensional magnitude of the complex pressure coefficient, Eq. (2.3)
E_k	$2s(s-3i)/g$

LIST OF SYMBOLS (Cont'd)

I_x, I_y	axial and transverse moments of inertia of the projectile.
J_0, J_1	Bessel function of the first kind, of order 0 or 1
\hat{K}	initial value of the complex yaw
$M_{L\hat{y}}, M_{L\hat{z}}$	transverse components of the liquid moment in an aeroballistic system
NS	Navier-Stokes
R	parameter associated with each eigenfrequency, Eq. (2.7)
Re	Reynolds number
SW	Stewartson-Wedemeyer
$\tilde{\alpha}$	angle of attack in an aeroballistic system
$\tilde{\beta}$	angle of side-slip in an aeroballistic system
δ_a	$(s-i)^{-1/2} Re^{-1/2}$
δ_c	$\frac{-(a/c)Re^{-1/2}}{2(1+is)} \left[\frac{1-is}{(s-3i)^{1/2}} - \frac{3+is}{(s+i)^{1/2}} \right]$
ϵ	damping rate per cycle of the coning motion
ϵ_{aj}	aerodynamic damping rate of the j-th arm, j=1,2
ϵ_j	damping rate of the j-th arm, j=1,2
ϵ_{kn}	damping rate for the liquid's (k,n)th wave mode
$\hat{\lambda}$	$\frac{[(3+is)(1-is)]^{1/2}}{1+is} \left(\frac{\pi}{2} \right)$
σ	I_x/I_y
τ	coning rate/ ϕ ; nondimensional coning frequency
τ_j	coning frequency for the j-th arm, j=1,2
τ_{kn}	eigenfrequency for the liquid's (k,n)th wave mode

LIST OF SYMBOLS (Cont'd)

$\dot{\phi}$	$\dot{\phi}t$
$\dot{\phi}$	spin rate
ϕ_p	orientation angle of the complex pressure coefficient, Eq. (2.3)

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Information Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314	1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299
1	Commander US Army Engineer Waterways Experiment Station ATTN: R.H. Malter Vicksburg, MS 39180	1	Director Benet Weapons Laboratory Armament RD&E Center US Army AMCCOM ATTN: SMCAR-LCB-TL Watervliet, NY 12189
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Commander US Army Aviation Research and Development Command ATTN: AMSAV-E 4300 Goodfellow Blvd St. Louis, MO 63120
1	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-TDC Dover, NJ 07801-5001	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
3	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-TSS Dover, NJ 07801-5001	1	Commander US Army Communications - Electronics Command ATTN: AMSEL-ED Fort Monmouth, NJ 07703-5301
6	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-LCA-F Mr. D. Mertz Mr. E. Falkowski Mr. A. Loeb Mr. R. Kline Mr. S. Kahn Mr. S. Wasserman Dover, NJ 07801-5001	1	Commander ERADCOM Technical Library ATTN: DELSD-L (Reports Section) Fort Monmouth, NJ 07703-5301
1	HQDA DAMA-ART-M Washington, DC 20310	1	Director US Army Missile and Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898-5500
		1	Commander US Army Tank Automotive Command ATTN: AMSTA-TSL Warren, MI 48397-5000

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Missile Command Research, Development, and Engineering Center ATTN: AMSMI-RD Redstone Arsenal, AL 35898	1	Commander US Army Development and Employment Agency ATTN: MODE-TED-SAB Fort Lewis, WA 98433
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range, NM 88002	3	Commander Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360
1	Commander US Army Jefferson Proving GD ATTN: STEJP-TD-D Madison, IN 47250	2	Commander David W. Taylor Naval Ship Research & Development Cmd ATTN: H.J. Lugt, Code 1802 S. de los Santos Bethesda, MD 20084
2	Commander US Army Research Office ATTN: Dr. R.E. Singleton Dr. Jagdish Chandra P.O. Box 12211 Research Triangle Park, NC 27709-2211	1	Commander Naval Surface Weapons Center ATTN: DX-21, Lib Br Dahlgren, VA 22448
1	AGARD-NATO ATTN: R.H. Korkegi APO New York 09777	3	Commander Naval Surface Weapons Center Applied Aerodynamics Division ATTN: M. Ciment A.E. Winklemann W.C. Ragsdale Silver Spring, MD 20910
2	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905	1	Director Office of Naval Research ATTN: Richard Whiting Code 123 800 Quincy Street Arlington, VA 22217
10	Central Intelligence Agency Office of Central Reference Dissemination Branch Room GE-47 HQS Washington, DC 20502	1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000
		1	AFWAL ATTN: J.S. Shang Wright-Patterson AFB, OH 45433

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	AFWAL ATTN: W. L. Hankey Wright-Patterson AFB, OH 45433	2	Director National Aeronautics and Space Administration Marshall Space Flight Center ATTN: A.R. Felix, Chief S&E-AERO-AE Dr. W.W. Fowlis Huntsville, AL 35812
1	Aerospace Corporation Aero-Engineering Subdivision ATTN: Walter F. Reddall El Segundo, CA 90245	3	Aerospace Corporation ATTN: H. Mirels R.L. Varwig Aerophysics Lab. P.O. Box 92957 Los Angeles, CA 90009
5	Director National Aeronautics and Space Administration Ames Research Center ATTN: D.R. Chapman W.C. Rose B. Wick P. Kutler Tech Library Moffett Field, CA 94035	2	Director Jet Propulsion Laboratory ATTN: L.M. Mach Tech Library 4800 Oak Grove Drive Pasadena, CA 91103
4	Director National Aeronautics and Space Administration Langley Research Center ATTN: E. Price J. South J.R. Sterrett Tech Library Langley Station Hampton, VA 23365	3	Arnold Research Org., Inc. ATTN: J.D. Whitfield R.K. Matthews J.C. Adams Arnold AFB, TN 37389
1	Director National Aeronautics and Space Administration Lewis Research Center ATTN: MS 60-3, Tech Lib 21000 Brookpark Road Cleveland, OH 44135-3127	3	Boeing Commercial Airplane Company ATTN: R.A. Day, MS 1W-82 P.E. Rubbert, MS 3N-19 J.D. McLean, MS-3N-19 Seattle, WA 98124
1	AVCO Systems Division ATTN: B. Reeves 201 Lowell Street Wilmington, MA 01887	1	Calspan Corporation ATTN: A. Ritter P.O. Box 400 Buffalo, NY 14225
		2	Lockheed-Georgia Company ATTN: B.H. Little, Jr. G.A. Pounds Dept 72074, Zone 403 86 South Cobb Drive Marietta, GA 30062

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	General Dynamics ATTN: Research Lib 2246 P.O. Box 748 Fort Worth, TX 76101	5	Sandia National Laboratory ATTN: H.W. Vaughn G. Wolfe W.L. Oberkampf F.G. Blottner G.F. Homicz Albuquerque, NM 87185
1	General Electric Company, RESD ATTN: W.J. East 3198 Chestnut Street Philadelphia, PA 19101	2	United Aircraft Corporation Research Laboratory ATTN: M.J. Werle Library East Hartford, CT 06108
2	Grumman Aerospace Corporation ATTN: R.E. Melnik L.G. Kaufman Bethpage, NY 11714	1	LTV Aerospace and Defense Co. Vought Missiles and Advanced Programs Division P.O. Box 650003 Dallas, TX 75265-0003
1	Lockheed Missiles and Space Company ATTN: Tech Info Center 3251 Hanover Street Palo Alto, CA 94304	2	Arizona State University Department of Mechanical and Energy Systems Engineering ATTN: G.P. Neitzel W. S. Saric Tempe, AZ 85287
3	Martin-Marietta Corporation ATTN: S.H. Maslen S.C. Traugott H. Obremski 1450 S. Rolling Road Baltimore, MD 21227	1	Cornell University Graduate School of Aero Engr ATTN: Library Ithaca, NY 14853
2	McDonnell Douglas Astronautics Corporation ATTN: J. Xerikos H. Tang 5301 Bolsa Avenue Huntington Beach, CA 92647	3	California Institute of Technology ATTN: Tech Library H.B. Keller, Math Dept D. Coles, Aero Dept Pasadena, CA 91109
1	Douglas Aircraft Company ATTN: T. Cebeci 3855 Lakewood Boulevard Long Beach, CA 90846	1	Director Johns Hopkins University Applied Physics Laboratory Johns Hopkins Road Laurel, MD 20707
3	Rockwell International Science Center ATTN: Dr. V. Shankar Dr. S. Chakravarthy Dr. N. Malmuth 1049 Camino Dos Rios Thousand Oaks, CA 91360		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Illinois Institute of Technology ATTN: S. Rosenblat H.M. Nagib 3300 South Federal Chicago, IL 60616	1	Northwestern University Department of Engineering Science and Applied Mathematics ATTN: Dr. S.H. Davis Evanston, IL 60201
2	Lockheed-Georgia Co. ATTN: B.H. Little, Jr. G. A. Pounds Dept. 72074, Zone 403 86 South Cobb Drive Marietta, GA 30063	2	Ohio State University Dept of Aeronautical and Astronautical Engineering ATTN: S.L. Petrie O.R. Burggraf Columbus, OH 43210
1	Vought Corporation ATTN: J.M. Cooksey, Chief Gas Dynamics Lab, 2-53700 P.O. Box 5907 Dallas, TX 75222	2	Polytechnic Institute of New York ATTN: G. Moretti Tech. Library Route 110 Farmingdale, NY 11735
1	The Johns Hopkins University Dept of Mech and Materials Sci. ATTN: S. Corrsin Baltimore, MD 21218	3	Princeton University James Forrestal Research Ctr Gas Dynamics Laboratory ATTN: S.M. Bogdonoff S.I. Cheng Tech Library Princeton, NJ 08540
1	Louisiana State University Dept. of Physics and Astronomy ATTN: Dr. R.G. Hussey Baton Rouge, LA 70803	1	Purdue University Thermal Science & Prop Ctr ATTN: Tech Library W. Lafayette, IN 47906
3	Massachusetts Institute of Technology ATTN: E. Covert H. Greenspan Tech Lib 77 Massachusetts Avenue Cambridge, MA 02139	1	Rensselaer Polytechnic Institute Department of Math Sciences ATTN: Tech Library Troy, NY 12181
2	North Carolina State Univ Mechanical and Aerospace Engineering Department ATTN: F.F. DeJarnette J.C. Williams Raleigh, NC 27607	1	Rutgers University Department of Mechanical, Industrial, and Aerospace Engineering ATTN: R.H. Page New Brunswick, NJ 08903
1	Notre Dame University Department of Aero Engr ATTN: T.J. Mueller South Bend, IN 46556		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Southern Methodist University Department of Civil and Mechanical Engineering ATTN: R.L. Simpson Dallas, TX 75272	1	University of California - San Diego Department of Aerospace Engineering and Mechanical Engineering Sciences La Jolla, CA 92037
1	Southwest Research Institute Applied Mechanics Reviews 8500 Culebra Road San Antonio, TX 78228	1	University of Santa Clara Department of Physics ATTN: R. Greeley Santa Clara, CA 95053
1	San Diego State University Department of Aerospace Engr and Engineering Mechanics College of Engineering ATTN: K.C. Wang San Diego, CA 92115	2	University of Cincinnati Department of Aerospace Engineering ATTN: R.T. Davis S.G. Rubin Cincinnati, OH 45221
1	Harvard University Division of Engineering and Applied Physics ATTN: G. J. Carrier Cambridge, MA 01238	1	University of Colorado Department of Astro-Geophysics ATTN: E.R. Benton Boulder, CO 80302
1	Stanford University Dept of Aeronautics/Astronautics ATTN: M. VanDyke Stanford, CA 94305	2	University of Maryland ATTN: W. Melnik J.D. Anderson College Park, MD 20740
1	Texas A&M University College of Engineering ATTN: R.H. Page College Station, TX 77843	1	University of Maryland - Baltimore County Department of Mathematics ATTN: Dr. Y.M. Lynn 5401 Wilkens Avenue Baltimore, MD 21228
1	University of California - Davis ATTN: H.A. Dwyer Davis, CA 95616	2	University of Southern California Department of Aerospace Engineering ATTN: T. Maxworthy P. Weidman Los Angeles, CA 90007
1	University of California - Berkeley Department of Aerospace Engineering ATTN: M. Holt Berkeley, CA 94720		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	University of Michigan Department of Aeronautical Engineering ATTN: W.W. Wilmarth Tech Library East Engineering Building Ann Arbor, MI 48104	1	University of Washington Department of Mechanical Engineering ATTN: Tech Library Seattle, WA 98105
2	University of Rochester Department of Mechanical and Aerospace Sciences ATTN: R. Gans A. Clark, Jr. Rochester, NY 14627	1	University of Wyoming ATTN: D.L. Boyer University Station Laramie, WY 82071
1	University of Virginia Department of Aerospace Engineering & Engineering Physics ATTN: I.D. Jacobson Charlottesville, VA 22904	1	University of Wisconsin - Madison Mathematic Research Center ATTN: John C. Strikwerda 610 Walnut Street Madison, WI 53706
1	University of California - Santa Barbara Department of Mechanical and Environmental Engineering ATTN: J.P. Vanyo Santa Barbara, CA 93106	1	Woods Hole Oceanographic Institute ATTN: J.A. Whitehead Woods Hole, MA 02543
1	University of Texas Department of Aerospace Engineering ATTN: J.C. Westkaemper Austin, TX 78712	2	Virginia Polytechnic Institute and State University Department of Aerospace Engineering ATTN: Tech Library Dr. T. Herbert Blacksburg, VA 24061
4	University of Virginia Department of Mechanical Aerospace Engineering ATTN: W. G. Wood R. J. Ribando R. Krauss W. E. Scott Charlottesville, VA 22904	<u>Aberdeen Proving Ground</u>	
1	University of Tennessee Department of Physics ATTN: Technical Library Knoxville, TN 37916	Director, USAMSAA ATTN: AMXS-D AMXS-MP, H. Cohen	
		Commander, USATECOM ATTN: AMSTE-TO-F	
		Commander, CRDC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-SPS-IL	

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report _____

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

(Remove this sheet along the perforation, fold as indicated, staple or tape closed, and mail.)

----- FOLD HERE -----

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-9989



----- FOLD HERE -----

END

DTIC

9-86